

PRODUCT SPECIFICATION SHEET

KGA 250

System specifications:

General	Diameter inside	DN/OD 250
	Material	PP
	Manhole	no
Construction	System	push fit system
	Chamber outside/inside	smooth/smooth
	Base outside/inside	smooth/smooth
	Shaft pipe outside/inside	smooth/smooth
Connection / Seals		DN/OD 160
	Pipe connections	EPDM (ball joint socket)
	Shaft connections	EPDM
	Cover	EPDM
	Telescope / Telescope manchette	SBR
Static	Max. installation depth	6,00 m
	Max. installation depth in groundwater	1,00 m
	Traffic load	LM1 according to DIN EN 1991-2/NA, rather: SLW60 according to DIN 1072
	Cover classes	A 15 - D 400
Approvals and relevant standards	Product standard	DIN EN 13598-2
	Seal	DIN EN 681
	Cover	DIN EN 124
	Application standard	DIN EN 476 DIN EN 752 DIN 1986
	Installation	DIN EN 1610
	Guidelines	ATV-DVWK-A 142 DWA-A 110 DVS 2207-4

System components:



Wavin Hungary | Új Gyártelep | 2072 Zsámbék | T +36 23 566 000 | F +36 23 566 001 | wavin@wavin.hu
 Connect to better at www.wavin.hu