

Grease separators for indoor installations

# Labko EuroREK® SL

## NS2...NS7 grease separators

### for cleaning greasy wastewater



The Labko grease separators are reliable entities manufactured in Finland and ready to be installed. They include a separator, a gastight cover and a grease alarm. These separator systems ensure that the sewer system operates faultlessly.

The Labko EuroREK SL grease separators are well-designed – they have a polished look and their design also enables quick and flexible installation as well as makes them durable and easy to maintain.

**wavin**



## Features

The EuroREK SL grease separators are intended to be installed inside the building above the floor, and they are suited to both new construction and renovated buildings. The sludge and grease room of the EuroREK NS2 and NS4 SL separators are located in the same single-section tank, whereas the EuroREK NS7 SL separator consists of two separate tanks.

### Light and slim

The tanks of the EuroREK SL grease separators are light and slim. The separators can easily fit through doorways and can be manoeuvred by two people. The frames of the separators have plenty of lifting lugs to ease transport and manoeuvring indoors.

### Easy to maintain and empty

The separator is easy to maintain through the gastight screw cap. The tanks are manufactured from durable and recyclable PE plastic. There are two alternative installation openings each for suction and ventilation pipes on top of the separators, which means that the handedness of the separators can be selected based on the installation site. The two tanks of the EuroREK NS7 SL separator can be installed in line or at an angle. The designer determines the desired installation solution, and the separator sockets are customised at the factory according to the specifications.

The EuroREK SL separators are emptied effortlessly and without odours from outside the property with the emptying pipe and suction box. These are available as accessories. The rotating washing nozzle is a new accessory available for the separators. It can be switched on during emptying to improve the process.

EuroREK SL	Length mm	Width mm	Height mm	Socket size mm	Weight kg
NS2 SL	1640	750	1670	D110	142
NS4 SL	2070	750	1670	D110	198
NS7 SL	Consists of separate NS2 and NS4 tanks, whose measurements are given above.				

## Applications

- Restaurants
- Bars
- Grills
- Small restaurants
- Canteens and lunchrooms

## Benefits and advantages

- Fulfils the requirements of the grease separator standard EN 1825
- Alarm system for grease room level and filling included as part of standard delivery
- Light to transport, quick and easy to install
- Slim model can fit into small spaces
- A Finnish quality product with a long life cycle
- The option to use suction emptying eases use of the product
- Easy to empty from outside with the suction box (IMUBOX) quick coupling case
- Gastight cover seals odours
- Handedness can be switched to suit the installation site
- Sampling coupling

### EuroREK grease separator accessories

(recommended for site-specific equipment)

- Data transfer unit
- IMUBOX and Tupla-IMUBOX (double suction box) quick coupling cases (suction pipes)
- Rotating washing nozzle

*EuroREK  
NS2...NS7 SL  
grease separator*

